



EU-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.



Certificate N° 0075/4626/162/08/22/1508

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : LINYI TONGFU SAFETY PRODUCTS CO.,LTD
No.5 Building, B1 Area, Lantian Intl.Trade Mall, Linxi 8 Road,
Linyi, Shandong
China

Description

PPE Type : *protective glove against mechanical risks*

Product reference : TF-L301

Article code : /

Glove description : YELLOW COTTON WITH LATEX COATED CRINKLE GLOVE

Available sizes : 6/XS - 11XXL

Pictures :



ATR:TF-L301

EN388



SIZE:10/XL LOT:XXXXX 2122X

No.5 Building,B1 Area,Lantian
Intl.Trade Mall,Linxi 8 Road,
Linyi,Shandong,China

Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

2 1 2 2 X

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from AUGUST 2022

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Didier GUISADO
Certification Manager



Date of first issue : 16 August 2022
End of validity date : 16 August 2027



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir: Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

LINYI TONGFU SAFETY PRODUCTS CO.,LTD

**MANUFACTURER'S TECHNICAL FILE TO THE
PPE REGULATION 2016/425**

Reference of the product	:	TF-L301
Article code	:	/
Technical file index	:	01
Last update	:	AUGUST 2022

IDENTIFICATION

Reference of the product :	:	TF-L301
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	AUGUST 2022

Manufacturer :

LINYI TONGFU SAFETY PRODUCTS CO.,LTD

No.5 Building, B1 Area, Lantian Intl.Trade Mall, Linxi 8 Road, Linyi, Shandong

China

tel : 0086-539-6373101

fax : 0086-539-6373102

Factory :

LINYI TONGFU SAFETY PRODUCTS CO.,LTD

No.5 Building,B1 Area,Lantian Intl.Trade Mall,Linxi 8 Road,Linyi,Shandong

China

tel: 0086-539-6373101

fax: 0086-539-6373102

GLOVE DESCRIPTION

General glove description and intended use:

YELLOW COTTON WITH LATEX COATED CRINKLE GLOVE

This glove is designed against mechanical risks.

Type of coating finish : crinkle

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒ Standard ☒ Instruction for use ☒ Marking
§1.4	Manufacturer's instructions and information is available	☒	☒ Standard ☒ Instruction for use ☐ Marking
§2.5	PPE which may be caught up during use	☒	☐ Standard ☒ Instruction for use ☐ Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒ Standard ☒ Instruction for use ☒ Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒ Standard ☒ Instruction for use ☒ Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		Green	Latex			0.95MM
		Yellow	Cotton	500 g/m ²	10G	
Back		Yellow	Cotton	500 g/m ²	10G	
Cuff		Yellow	Cotton/ Elastic	520g/m ²	10G	
Binding		Red/ Black/ Yellow/ Brown	Polyester/ cotton			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : Level 5

Available size range: 6/XS - 11XXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S220703865_2 S220703870_2 (DMFu) S220703873_2	
EN 388	S220703865_2	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : TF-L301

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Method of marking on the glove :

Print on the back

Packaging suitable for transport:

12 pairs/polyester bag,240pairs/carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

- 1.We choose the good suppliers to provide us material with good quality. At the same time, when we received the raw materials we should test some items according to relevant standard, such as EN388,EN ISO 21420 ; the bad material cannot meet requirement will be rejected.
- 2.when we received the raw materials for mass production, the material QC will check them serious in order that no any problem at the beginning;
- 3.Make samples before production,make sure samples meet the requirement of client and EN388,EN ISO 21420 and other chemical items ,then start to produce; it's very important for us;
- 3.Regularly check the quality of products in the whole process;any unacceptable defects are found, the gloves will be discarded; QC for each step will perform inspection in accordance with our requirement strictly;
- 4.Confirm packing specification before packing and regularly check and keep records;
- 5.According to QA inspection procedures,QA will perform final inspection on some cartons of glove randomly. Then the goods can be shipped in case no any problems.Our QC will pick up some samples and test EN388 once a year.

INSTRUCTION FOR USE

LINYI TONGFU SAFETY PRODUCTS CO.,LTD

No.5 Building, B1 Area, Lantian Intl.Trade Mall, Linxi 8 Road, Linyi, Shandong
China

Glove reference : TF-L301
Article code: /
User notice index : 01
Last update : AUGUST 2022

Glove description :

YELLOW COTTON WITH LATEX COATED CRINKLE GLOVE

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE



SIZE:10/XL LOT:XXXXX 2122X

No.5 Building,B1 Area,Lantian
Intl.Trade Mall,Linxi 8 Road,
Linyi,Shandong,China

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: Level 5

Available size range: 6/XS - 11/XXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications :

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN
388:2016 + A1:2018



2 1 2 2 X

Levels of performance



Read carefully the instructions for use provided with the product

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Contains natural rubber latex, which could cause allergic reactions, including anaphylactic choc.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.

Available on : <http://lywithrich.en.alibaba.com>