



Notified body N° 0075

EC-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N°

0075/1120/162/02/16/0202

Is given to the following model of personal protective equipment :

Issued to : SHANDONG XINGYU GLOVES CO.,LTD

MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY
SHANDONG PROVINCE

CHINA

Distributor : /

Product reference : PU-1101

Description :

PPE Type : *Protective gloves against mechanical risks.*

Reference standard : *EN 388 : 2003.*

Category : *II*

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the complete certificate N°0075/1120/162/02/16/0202.

Issued in Lyon by Lionel Gaudillere
Head of CE marking

Date of issue : February 24th, 2016



In application of the Directive ref 89/686/EEC of the 21th December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decree N°92-765, 766 and 768 of the 29th July 1992 concerning the transposition of this Directive into French law. CTC is notified by decree of the Ministry of work of the 20th December 2010 and is registered under the number 0075 in OJEU.



4 rue Hermann Frenkel 69367 Lyon cedex 07 FRANCE
Tel : 33 472 761 010 - Fax : 33 472 761 000 - email : ctclyon@ctcgroupe.com - www.ctc.fr
Comité professionnel de développement économique cuir chaussure maroquinerie
Siret 77564972600160 - code NAF 9412Z - TVA FR 88775649726





In application of the Directive ref. 89/686/EEC of the 21st of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29th of July 1992 concerning the transposition of this Directive into French law,

CTC

4, rue Hermann Frenkel - 69367 Cedex 07 - France

Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr

authorized by decrees of the Ministry of Work, Employment and Health of the 20th of December 2010,
registered under the number 0075, published in OJEC, delivers :

EC-TYPE EXAMINATION CERTIFICATE **0075/1120/162/02/16/0202**

To the following model of personal protective equipment :

- * reference of the model : PU-1101
- * protective glove against mechanical risks.
- * Manufacturer :

SHANDONG XINGYU GLOVES CO.,LTD

**MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY SHANDONG
PROVINCE**

CHINA

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on February 24th, 2016

Issued by Lionel GAUDILLERE



NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.

1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index : 01

Reference : PU-1101

Basic Model

Dated : FEBRUARY, 2016

13G Polyester Glove Coated With PU

Available sizes :

7/S 8/M 9/L 10/XL 11/XXL

Visual description :



Material :

	Color	Material	Gauges	Thickness
PALM	black	PU		
	black	polyester	13gauges /inch	
BACK	black	polyester	13gauges /inch	
LINING				
CUFF	black	polyester /elastic	13gauges /inch	
BINDING	Black	polyester		

2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- * EN 420:2003+A1:2009 - General requirements for gloves and test methods
- * EN 388:2003 - Protective glove against mechanical risks
- * At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)
- * This product is a category II.

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	CTC	Other
EN 420	SH60090-14, SH60180-14	
Azo	SH60090-14	
EN 388	SH60090-14, SH60180-14	
OTHER	SH60090-14 (DMFu, Tin, Cad)	

Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
3	1	3	1

The levels of performance have been measured on the palm

3. MARKING

Each glove is clearly marked with the following information:

- * Logo of the authorized representative:
- * **CE** marking
- * reference of the model: PU-1101
- * size
- * pictogram for mechanical risks followed by the performance levels
- * information pictogram

Marking example:



SHANDONG XINGYU GLOVES CO.,LTD

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	PU-1101
Technical file index	:	01
Last update	:	FEBRUARY, 2016

IDENTIFICATION

Reference of the product :	:	PU-1101
Basic model	:	
Technical file index :	:	01
Last update :	:	FEBRUARY, 2016

Manufacturer :

SHANDONG XINGYU GLOVES CO.,LTD

MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY SHANDONG
PROVINCE

CHINA

tel : 0086-536-2587338

fax : 0086-536-2586328

Factory :

SHANDONG XINGYU GLOVES CO.,LTD

MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY SHANDONG
PROVINCE

CHINA

tel: 0086-536-2587338

fax: 0086-536-2586328

GLOVE DESCRIPTION

Glove description :

13G Polyester Glove Coated With PU

Visual description:



Available sizes :

Minimum length of glove (mm)	Sizes
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
PALM		black	PU	75g/m2		
		black	polyester	160g/m2	13gauges /inch	
BACK		black	polyester	160g/m2	13gauges /inch	
LINING						
CUFF		black	polyester /elastic	310g/m2	13gauges /inch	
BINDING		Black	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5

PH of glove and lining is greater than 3.5 and lower than 9.5 : yes

Chromium VI lower than the detection limit : conform

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2003

Protection offered	Performance levels
Abrasion resistance	3
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1

The levels of performance have been measured on the palm

TEST REPORTS

Laboratory	CTC	Other
EN 420	SH60090-14, SH60180-14	
Azo	SH60090-14	
EN 388	SH60090-14, SH60180-14	
OTHER	SH60090-14 (DMFu, Tin, Cad)	

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : PU-1101

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :



Method of marking on the glove :

printed on the back

Packaging :

1 doz/pe bag, 10 doz/carton

MEANS OF CONTROL

We control quality according to the requirement of ISO 9001 : 2008



INSTRUCTION FOR USE

SHANDONG XINGYU GLOVES CO.,LTD

MIDDLE YAOQIAN ROAD CHAOYANG DISTRICT GAOMI CITY SHANDONG PROVINCE
CHINA

Glove reference : PU-1101

Available sizes : 7/S 8/M 9/L 10/XL 11/XXL

Glove description :

13G Polyester Glove Coated With PU

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :



Application :

Mechanical hazard - EN 388



3131

Levels of performance

Abrasion resistance	3	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.