



## Extrusion for Commercial Retail & Residential Application

Razor series offer high-efficiency illumination with a sleek design available in white or black finishes. It features superior lighting performance and versatile mounting options, with dimming controls and a long lifespan ensuring reliable and customizable lighting solutions.



## LUMINAIRE SPECIFICATION

### Light Source Data

|                        |                                  |
|------------------------|----------------------------------|
| System Power (W/m)     | 11.6 @ 4000 K                    |
| Delivered Lumen (lm/m) | 722 @ 4000 K                     |
| Efficacy (lm/W)        | 62.2 @ 4000 K                    |
| CCT (K)                | 2700 / 3000 / 3500 / 4000 / 5000 |
| Beam Angle             | 110 °                            |
| CRI                    | 90                               |
| SDCM                   | <3                               |

### General Data

|                   |                                    |
|-------------------|------------------------------------|
| Mounting          | Recessed                           |
| Dimension (mm)    | 47 (W) x 56 (H)                    |
| Cutout (mm)       | 37                                 |
| Finish            | White / Black                      |
| IP Rating         | 20                                 |
| Lifetime (L80B10) | 50,000hrs                          |
| Dimming Control   | Phase cut / 0-10V / DALI / Casambi |
| Warranty          | 5 years                            |

